Risk Assessment for Grounds Maintenance Activities OSC



Sco	Scope of Risk Assessment This assessment covers all OSC club members, visitors and contractors anywhere on OSC property at any time										
Date	Date of Assessment4th January, 2013						Last Reviewed29th April,2021, Matt Thomas				
Ass	essor's Details	Assessed by Matthew Thomas	s (OS	SC Co	ommittee	Member) Tel:	0775 953 9028				
	Description of Hazard and Expected Consequence		Potential for Harm Likelihood x Severity = Risk Level					Residual Risk Likelihood x Severity = Risk Level			
No			L	s	Risk Leve I	нмс	Control Measures		s	Risk Leve I	нмс
1	Injuries caused by Slips, ⊺	Trips and falls	3	3	9	Medium	Footwear appropriate to the ground surface, task and particular location must be worn. Buoyancy Aids (PFD's) must be worn when close to the water's edge. Working at height to be avoided where possible. Special care to be taken on slipways, pontoons and island. No lone access is allowed on the island.	2	2	4	Low
2	Cuts and other injuries fro vegetation etc.	om tooling, machinery and	4	5	20	High	Appropriate cut-resistant gloves to be worn when handling sharp tools. Mechanical cutting equipment belonging to OSC only to be used by those persons deemed competent to do so by a quorum of the committee. Mechanical cutting equipment, whether it is owned by OSC or not, must only be used with the appropriate PPE including, where necessary, eye and hearing protection for other persons in the vicinity of the task. Consideration should be given to cordoning off the work area to discourage unauthorised access for the duration of the task. Gardening type gloves and clothing to resist cuts and scratches to be worn when working with thorny vegetation.	3 3 9 Medium		Medium	

SEVERITY				
CATEGORY	DEGREE	DESCRIPTION		
1	INSIGNIFICANT	Minor injury to personnel Minor damage to equipment		
2	MINOR	Injury to personnel Damage to equipment		
3	REPORTABLE	Injury resulting in loss of time Moderate damage to equipment		
4	MAJOR	Serious injury to personnel Major damage to equipment		
5	CATASTROPHIC	Fatal /disability injury to personnel Total equipment loss		

LIKELIHOOD LEVEL					
LEVEL	DESCRIPTION	INDIVIDUAL FAILURE MODE			
1	REMOTE	So unlikely that occurrence may not be experienced			
2	UNLIKELY	Unlikely, but possible to occur during project			
3	OCCASIONAL	Likely to occur sometime during project			
4	PROBABLY	Will occur several times during project			
5	FREQUENTLY	Likely to occur frequently during project			

	LIKELIHOOD LEVEL					
SEVERITY CATEGORY	1	2	3	4	5	
5	5	10	15	20	25	
4	4	8	12	16	20	
3	3	6	9	12	15	
2	2	4	6	8	10	
1	1	2	3	4	5	

	ACTION CRITERIA
12 - 25	High – Unacceptable – further assessment or action required to reduce risk to as low as reasonably practicable
5 – 10	Medium- Further assessment or action may be required if the team consider the risk not to be as low as reasonably practicable
1-4	Low- Acceptable – Adequate safeguards are in place